

Thermostats

Quick Start Guide



warmboard[®]
COMFORT SYSTEM

The Warmboard thermostats are an integral part of the **Warmboard Comfort System**. It's very important they are installed correctly to ensure the system operates properly. Follow these simple steps and refer to the complete installation guide for additional information as needed.



Thermostats should be installed after texture and paint. Each thermostat will be snapped into a pre-wired J-Box (at least 18 cu. inches). Once the Warmboard thermostats are powered up, they communicate wirelessly, so now additional wiring is required.

- 1 Each thermostat is labeled by room. Review the Plan Set to confirm where each thermostat should be installed. It is very important to install each thermostat into the proper location.
- 2 Gripping the sides of the thermostat with one hand, and the with the other, separate the front and back pieces from each other.
- 3 Wire the back of the thermostat into the J-Box, then fasten with the provided screws.
- 4 Hold the front portion of the thermostat by the sides, then slide in and reconnect to the back portion of the thermostat.

Declaration of Conformity
47 CFR § 2.1077 Compliance Information

Warmboard Bridge // FCC ID: 2ASM7-WBR01

Responsible Party – U.S. Contact Information

Warmboard Inc.
8035 Soquel Drive, Suite 41
Aptos, California 95003 USA

877.338.5493 // warmboard.com

FCC Compliance Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. When using this device, a distance of 20cm to the user should always be maintained.

This radio transmitter (24839-WBR01) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device. When using this device, a distance of 20cm to the user should always be maintained. -10dBi PCB antenna.

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent émetteur radio (24839-WBR01) a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur. Lors de l'utilisation de cet appareil, une distance de 20 cm par rapport à l'utilisateur doit toujours être maintenue. Antenne de carte PCB -10dBi.

Cet appareil contient des émetteurs / récepteurs exemptés de licence conformes aux RSS (RSS) d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes:

1. Cet appareil ne doit pas causer d'interférences.
2. Cet appareil doit accepter toutes les interférences, y compris celles susceptibles de provoquer un fonctionnement indésirable de l'appareil.



Warmboard, Inc.
8035 Soquel Drive, Suite 41
Aptos, California 95003

1.877.338.5493
warmboard.com

