

Thank you for choosing
Warmboard.



Say Hello to your Warmboard Bridge!

As the final piece to your Warmboard Comfort System, the Bridge securely connects to the Internet to update essential software and maintain an accurate date and time across all thermostats. The Bridge also allows us to remotely diagnose performance issues without compromising your privacy. Finally, you will be able to use your smart phone to access Vacation Mode, a setting which maintains a minimum temperature of 55°F while you are away for extended periods of time.

For more information about your new heating system, visit [**warmboard.com**](http://warmboard.com).

- 1 Remove the Bridge and Ethernet cable from this box.
- 2 Download the Warmboard vacation app to your iOS or Android device. Create an account, then scan the large QR code on the side of the Bridge.
- 3 Connect one end of the Ethernet cable to an available port on your Internet router. Next, connect the other end of the cable to the Bridge.
- 4 Plug the Bridge into a power outlet and wait for the steady green light to confirm a successful connection to the application server.

Declaration of Conformity

47 CFR § 2.1077 Compliance Information

Warmboard Bridge // FCC ID: 2ASM7-WBR01

Responsible Party – U.S. Contact Information

Warmboard Inc.
100 Enterprise Way, Suite G300
Scotts Valley, California 95066 USA

warmboard.com // 800.556.0595

FCC Compliance Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. When using this device, a distance of 20cm to the user should always be maintained.

This radio transmitter (24839-WBR01) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device. When using this device, a distance of 20cm to the user should always be maintained. 1.9dBi PCB antenna.

This device contains license-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's license-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.
2. This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent émetteur radio (24839-WBR01) a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur. Lors de l'utilisation de cet appareil, une distance de 20 cm par rapport à l'utilisateur doit toujours être maintenue. Antenne de carte PCB 1.9dBi.

Cet appareil contient des émetteurs / récepteurs exempts de licence conformes aux RSS (RSS) d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes:

1. Cet appareil ne doit pas causer d'interférences.
2. Cet appareil doit accepter toutes les interférences, y compris celles susceptibles de provoquer un fonctionnement indésirable de l'appareil.



warmboard.com // 800.556.0595